



MANUFACTURER OF CONSTRUCTION CHEMICALS

PROPERTIES:

Aspect	Grey coloured fluid of mixed material.
Mixed ratio	Pack A : Pack B = 2 : 1
Pot life (at 27°C)	30-40 minutes.
Full cure at Ambient temp.	4-5 days.
Compressive strength (kg/cm ²)	600 (minimum)

SHELFLIFE:

24 months from the date of manufacture in unopened condition.

PACKING:

1.2 kg (Pack A 0.8 kg and Pack B 0.4 kg) and as required.

HANDLING PRECAUTION:

Eposet BA may cause irritation of the skin to some individuals if incorrectly handled. The component should not be allowed in direct contact with the skin. Rubber gloves should be worn for effective protection.

NOTE:

- Eastern Setcrete has a team of trained professionals to provide technical support to your problems in construction, particularly to recommend the correct product for a specific application. We can also send our authorized applicator to apply our products at your site.
- Contents of this data sheet are only indicative and not conclusive. All the results shown here are generated from our laboratory or from our own site experiences.
- The quality of all our products are maintained as per ISO:9001 recommendations and continuous research, but conditions prevailing at the point of application can vary its behavior.



Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.
Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,
Website : www.setcrete.com

