



An ISO 9001 : 2000 Company

**MANUFACTURER OF CONSTRUCTION CHEMICALS**

## SETCRETE CRM

### PRODUCT DATA SHEET

**POLYMER MODIFIED REPAIR MORTAR.**

#### DESCRIPTION:

**Setcrete CRM** is a thixotropic polymer modified, cement based two component systems. When mixed together, the components react to form a high strength repair and leveling mortar for concrete.

#### USES:

Easy to use concrete repair mortar suitable for water retaining structures, top sealing, damaged edges and joint areas; repairing of honeycombing and channels.

#### ADVANTAGES:

- High strength repair and leveling mortar for concrete.
- Good water & oil resistance.
- High mechanical strength.
- Good bond strength.



#### APPLICATION:

Comp.A and Comp.B should be mixed in the ratio 1: 6 by weight. Mixing to be done in low speed mixer. Substrate concrete to be cleaned and saturated thoroughly with water. Apply the mortar vigorously onto the damp surface. Curing should be done with moist cloth for 3 days and then left for air cure.

#### PROPERTIES:

Aspect	Comp. A – Liquid , Comp. B – Grey Powder.
Mixing Ratio	Comp.A : Comp. B = 1 : 6 by weight.
Mixed Density	2.1 to 2.3 Kg / Lit.
Workable time	25 +/- 5 minutes, at 27 deg.C
Compressive strength	300 Kg/Sq.Cm, (after 28 days)

JAS-ANZ



#### Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.

Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,

Website : www.setcrete.com

