



PROPERTIES:

Form	Liquid
Colour	Silver Grey
Specific Gravity	0.85 - 0.87 at 27°C
Non-volatile solid content	19 ± 2%
Coverage	6 to 7 Sq. Metre/lit.

Application by spray or brush. The coverage depends on site condition such as wind velocity, temperature and humidity.

Setcrete RAP complies with ASTM C-309-81. It dries like pigmented lacquer when sprayed/ brushed into newly laid concrete surface not containing surface water. The evaporation rate of water from inside the membrane film is as low as 0.30 kg. against 0.55 kg(Maximum) per square metre per 24 hours stipulated in ASTM/BS/MOST (Government of India) specification.

SHELF LIFE:

For best result use before one year.

PACKING:

5, 20,100 lit in HDPE container or as required.

HANDLING PRECAUTION:

Setcrete RAP is non-toxic but ingestion is to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

NOTE:

- Eastern Setcrete has a team of trained professionals to provide technical support to your problems in construction, particularly to recommend the correct product for a specific application. We can also send our authorized applicator to apply our products at your site.
- Contents of this data sheet are only indicative and not conclusive. All the results shown here are generated from our laboratory or from our own site experiences.
- The quality of all our products are maintained as per ISO:9001 recommendations and continuous research, but conditions prevailing at the point of application can vary its behavior.

Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.
Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,
Website : www.setcrete.com

JAS-ANZ

