



EASTERN SETCRETE *Private Limited*

An ISO 9001 : 2000 Company

MANUFACTURER OF CONSTRUCTION CHEMICALS



SETFLEX WP

PRODUCT DATA SHEET

ACRYLIC MODIFIED POLYMER FOR WATERPROOFING.

DESCRIPTION:

Setflex WP is an acrylic polymer and when used as recommended, combines with cement and fine sand to form an impermeable coating by blocking the capillaries and pores of the substrate.

USES:

In all structures that are required to be waterproofed and protected against the ingress of moisture, like Basements, Water tanks, Swimming Pools, Retaining Walls, Bridge Walls, Tunnels, Sewage Tanks, reservoirs, Dams, Dock gates, Roof top & parapet wall. General concrete repair, protection of concrete against corrosion, salt attack etc.

ADVANTAGES:

- Excellent adhesion to most building material.
- Reduces or prevents salt penetration into concrete.
- Low permeability makes mortar or concrete water proof.
- Imparts chemical resistance to substrate.



APPLICATION:

Surface preparation: Substrate must be sound, clean and free from loose particles or laticence and preferably be wire brushed. Cracks must be treated first depending on the type of crack. The prepared surface must be thoroughly wetted with water for absorption and excess water is to be removed.

Mixing: **Setflex WP** should preferably be mixed mechanically by using an electrical drill with paddle attachment. Pour the **Setflex WP** in the container first and add cement and fine sand (500 micron down) slowly, and mixing continuously until an even homogeneous mix of brushing consistency is obtained.

Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.

Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,

Website : www.setcrete.com

JAS-ANZ

