



An ISO 9001 : 2000 Company

MANUFACTURER OF CONSTRUCTION CHEMICALS



SETPLUG

PRODUCT DATA SHEET

A QUICK SETTING HYDRAULIC COMPOUND.

DESCRIPTION:

It is a fast setting hydraulic compound for stopping running water

USES:

- It is used to stop running water and seepage through concrete and masonry walls, dams etc.

ADVANTAGES:

- Stops running water immediately
- Non shrink and non-metallic
- High strength
- Easy to use
- Sets under water

APPLICATION :

Chisel the masonry around the crack to a width & depth not less than 25 mm. The hole should be wider within the wall than at the surface. Mix Setplug in the ratio of 0.28 to 0.33 (Water/powder ratio). Force the material into the crack when heat generation is felt. Hold tightly with hand for 3 minutes.

PROPERTIES:

Aspect	Light brown powder
Setting time at 27 deg. C	1 to 3 minutes
Compressive strength at 27 deg. C	80 Kg/Sq. Cm (minimum) after 1 hour
	190 Kg/Sq.Cm (minimum) after 24 hour



Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.
 Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,
 Website : www.setcrete.com

JAS-ANZ

