



## PROPERTIES:

Aspect of comp. A	White paste
Aspect of comp. B	Dark brown paste
Shore "A" Hardness	20 to 25
Pot Life at 27°C	4 hours (minimum)
Curing at 27°C	7 days (Trafficable after 24 hours)

## SHELF LIFE:

12 months from the date of manufacture in unopened condition. Keep in cool and dry place.

## PACKING :

4 kg in tin container.

## HANDLING PRECAUTIONS:

**Setsealant** is non-toxic and ingestion to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

## NOTE:

- Eastern Setcrete has a team of trained professionals to provide technical support to your problems in construction, particularly to recommend the correct product for a specific application. We can also send our authorized applicator to apply our products at your site.
- Contents of this data sheet are only indicative and not conclusive. All the results shown here are generated from our laboratory or from our own site experiences.
- The quality of all our products are maintained as per ISO:9001 recommendations and continuous research, but conditions prevailing at the point of application can vary its behavior.

### Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.  
Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,  
Website : www.setcrete.com

JAS-ANZ

