



PROPERTIES:

Form	Liquid aqueous dispersion
Specific Gravity	1.4 ± 0.05
Solubility	Freely mixable with water
pH	2-3
Setting Time (Tested using	Initial setting time 1 to 3 min.
Gillmore Apparatus As per ASTM)	Final setting time not more than 12 min.

SHELF LIFE:

6 months from the date of manufacture.

The material should be stored under shed and away from source of heat.

PACKING:

10, 25, 140, 250 kg, in HDPE container or as required.

HANDLING PRECAUTION:

Setshot LAF is to be stored in a proper place, away from sunlight or other heat source. Any contact with the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

NOTE:

- Eastern Setcrete has a team of trained professionals to provide technical support to your problems in construction, particularly to recommend the correct product for a specific application. We can also send our authorized applicator to apply our products at your site.
- Contents of this data sheet are only indicative and not conclusive. All the results shown here are generated from our laboratory or from our own site experiences.
- The quality of all our products are maintained as per ISO:9001 recommendations and continuous research, but conditions prevailing at the point of application can vary its behavior.

Corporate Office:

P-89, C.I.T. Road, Kolkata - 700 010 Phone : 2353-9279 / 23632470.

Fax : 91-33-23733078 E-mail : setcrete@yahoo.com,

Website : www.setcrete.com

JAS-ANZ

